

Package: lglasso (via r-universe)

October 8, 2026

Type Package

Title Graphical Lasso for Longitudinal Data

Version 2.1.0

Description Estimate treatment-specific precision matrices (networks) from longitudinal high-dimensional normal data. The corresponding random effects are also estimated. It is motivated by the analysis of omics data in clinical trials where the longitudinal omics data becomes increasingly common. It includes both one-stage models (without treatment) and two-stage models (with one treatment). For details of the algorithms, please check the materials on its GitHub repo. If you have any questions, feel free to contact the maintainers through the email below.

License GPL (≥ 3)

Encoding UTF-8

LazyData true

URL <https://github.com/jiezhou-2/lglasso>

Suggests knitr, rmarkdown, testthat ($\geq 3.0.0$)

Depends R (≥ 3.5)

NeedsCompilation no

Author Jie Zhou [aut, cre, cph], Jiang Gui [aut], Weston Viles [aut],
Anne Hoen [aut]

Maintainer Jie Zhou <chowstat@gmail.com>

LinkingTo Rcpp, RcppArmadillo

Imports parallel, pheatmap, RColorBrewer, Rcpp, doParallel, foreach

Roxygen list(markdown = TRUE)

RoxygenNote 7.3.3

Config/testthat/edition 3

Repository <https://jiezhou-2.r-universe.dev>

Date/Publication 2026-10-07 22:29:43 UTC

RemoteUrl <https://github.com/jiezhou-2/lglasso>
RemoteRef HEAD
RemoteSha 46a313fd3c82477376b0a814a5ad4d0461869989

Contents

CVlglasso	2
lglasso	3
Simulate	6
Index	8

CVlglasso	<i>Cross validation for lglasso</i>
-----------	-------------------------------------

Description

The function computes the cross validation errors in lglasso.

Usage

```
CVlglasso(  
  data,  
  K,  
  group = NULL,  
  random = FALSE,  
  lambda = NULL,  
  nlam = 10,  
  lam.min.ratio = 0.01,  
  expFix = 1,  
  trace = FALSE  
)
```

Arguments

data	same as in lglasso
K	fold number for the cross validation
group	same as in lglasso
random	same as in lglasso
lambda	tuning parameter. For one-stage model, lambda is a vector. For two-stage model, lambda is a 2-column matrix. The first column is tuning parameter controlling the sparsity, the second column is tuning parameter controlling the similarity of two networks.
nlam	If lambda is NULL, then nlam set the number of tuning parameter
lam.min.ratio	ratio of largest lambda vs smallest lambda
expFix	same as in lglasso
trace	logical variable. Whether show the computation process

Value

list of length 2. The first component is the cross validation errors, the second component is the corresponding tuning parameters

lglasso

Longitudinal graphical lasso

Description

This function estimates precision matrices(networks) and random effects from longitudinal high-dimensional data under normality assumption.

Usage

```
lglasso(
  data,
  lambda,
  group = NULL,
  random = FALSE,
  expFix = 1,
  N = 100,
  maxit = 50,
  tol = 10^(-2),
  lower = c(0.01, 0.01),
  upper = c(10, 10),
  w.init = NULL,
  wi.init = NULL,
  trace = FALSE,
  ...
)
```

Arguments

data	n by (p+2) data frame in which the first column is subject IDs, the second column is the time points of longitudinal data.
lambda	numerical vector of tuning parameters. For one-stage model, lambda is a scalar controlling the sparsity of the network. For two-stage model, lambda is a vector of length 2, in which the first entry controls the sparsity of both pre-treatment and post-treatment networks, while the second entry controls the overlap of the two networks.
group	factor of length n if supplied. If group is a one-level factor, then a one-stage model is fitted. If group is a two-level factor, then a two-stage model is fitted. Data points that are before (after) the treatment (exposure) share the same level in group. If NULL, then a one-stage model is fitted.
random	a logical variable. If TRUE, then a heterogeneous model is fitted. Otherwise, a homogeneous model is fitted.

expFix	numerical number specifying the exponent in the covariance function of the longitudinal data. Default is 1.
N	a integer specifying the number of sampling for heterogeneous model
maxit	integer specifying the maximum iterations for the algorithms.
tol	a small number determining whether the algorithms converged and should stop.
lower	vector of length 1 or 2 which specifies the lower bounds for temporal correlation tau. It is of length 1 for one-stage model and 2 for two-stage model
upper	vector of length 1 or 2 which specifies the upper bounds for temporal correlation tau. It is of length 1 for one-stage model and 2 for two-stage model
w.init	initial value for covariance matrix. Default is identity matrix.
wi.init	initial value for precision matrix. Default is identity matrix.
trace	whether or not show the progress of the computation
...	other inputs

Details

lglasso is developed to estimate precision matrices, or networks, and random effects τ_i from high-dimensional longitudinal data. The one-stage model in lglasso is proposed in Zhou *et al* (2024). Currently, it contains two network identification models, *i.e.*, one-stage and two-stage model. One-stage model assume a common network underlying the longitudinal data for all the subjects. Consequently, the function outputs a single network as the estimate in this case. In two-stage models, a treatment is applied at time t_i during the time interval for subject i . Therefore, there are two networks, *i.e.*, pre- and post-treatment networks, that need to be estimated simultaneously. For details, please check the reference paper and the online resources.

Value

A list which includes:

w: the list of the estimates for covariance matrices

wi: the list of the estimates for precision matrices

tau: the estimate of dampening rate tau. For heterogeneous models, the output is a vector called random effects. For homogeneous model, the output is a scalar.

alpha: a scalar representing the estimate of the parameter in exponential distribution of tau for heterogeneous models. The output is NULL for homogeneous model

ll: the likelihood. ll is used to compute extended QIC for tuning parameter selection

Examples

```
## Not run:
library(lglasso)
# number of nodes
p=15
# number of edge in general network
m1=20
# the difference between the number of edges in individual networks and general network
```

```

m2=5
# number of subjects
n=30
set.seed(1)
## One-stage model
### Estimate the network based on homogeneous one-stage model
####simulate data
dd=Simulate(type="homo",n=n,p=p,m1=m1,m2=m2,tau=2,tt=10)
ddata=dd$data
dim(ddata)
ddata[1:2,1:5]
#### Estimation
aa=lglasso(data=ddata,lambda = 0.01,trace=TRUE)
estimates=lapply(aa$wi,function(ll){ifelse(abs(ll)>10^(-5),1,0)})
#### estimated network
estimates
#### true network
dd$network
#### correlation parameter
aa$tau
#### likelihood
aa$ll

### Estimate the network based on heterogeneous one-stage model
####simulate data
dd=Simulate(type="heter",n=n,p=p,m1=m1,m2=m2,tt=10,alpha=5,group = 1)
ddata=dd$data$pre
dim(ddata)
ddata[1:2,1:5]
#### Estimation
aa=lglasso(data=ddata,lambda = 0.01,random=TRUE,trace=TRUE)
estimates=lapply(aa$wi,function(ll){ifelse(abs(ll)>10^(-5),1,0)})
#### estimated network
estimates
#### true network
dd$network
#### likelihood
aa$ll

## Two-stage model
### Estimate the networks based on homogeneous two-stage model
####simulate data
dd=Simulate(type="homo",n=n,p=p,m1=m1,m2=m2,tau=c(2,1),tt=10)
ddata=do.call(rbind,dd$data)
group=c(rep(0,nrow(ddata)/2),rep(1,nrow(ddata)/2))
dim(ddata)
ddata[1:2,1:5]
#### Estimation
aa=lglasso(data=ddata,lambda = c(0.01,0.01),group = group,trace=TRUE)

```

```

estimates=lapply(aa$wi,function(ll){ifelse(abs(ll)>10^(-5),1,0)})
#### estimated pre-treatment network
estimates[[1]]
#### true pre-treatment network
dd$network$pre
#### estimated post-treatment network
estimates[[2]]
#### true post-treatment network
dd$network$post
#### correlation parameters
aa$tau
#### likelihood
aa$ll

### Estimate the networks based on heterogeneous two-stage model
####simulate data
dd=Simulate(type="heter",n=n,p=p,m1=m1,m2=m2,tt=10,alpha=0.5,group=2)
ddata=do.call(rbind,dd$data)
group=c(rep(0,nrow(ddata)/2),rep(1,nrow(ddata)/2))
dim(ddata)
ddata[1:2,1:5]
#### Estimation
aa=lglasso(data=ddata,lambda = c(0.01,0.01),random=TRUE,group = group,trace=TRUE)
estimates=lapply(aa$wi,function(ll){ifelse(abs(ll)>10^(-5),1,0)})
#### estimated pre-treatment network
estimates[[1]]
#### true pre-treatment network
dd$network$pre
#### estimated post-treatment network
estimates[[2]]
#### true post-treatment network
dd$network$post
#### likelihood
aa$ll

## End(Not run)

```

Simulate

Simulate longitudinal data from one-stage/two-stage model

Description

This function randomly generates precision matrices (networks) and then simulates normal data that follows these network structures.

Usage

```

Simulate(
  type = c("homo", "heter"),

```

```
n,  
p,  
m1,  
m2,  
tt,  
tau,  
alpha = 1,  
group = 1  
)
```

Arguments

type	which type of data you are generating. There are two options. One is homo which generates subjects with identical temporal correlation parameter. The other is heter which generates subjects with different temporal correlation parameter.
n	the number of subjects in the data set
p	the dimension of the normal distribution
m1	the number of edges in true networks
m2	the edge difference between two networks
tt	the average time points for each subject
tau	the true dampening rate in homogeneous models
alpha	the true parameter in exponential distribution of tau when type is heter
group	a scalar of 1 or 2, indicating one-stage or two-stage model.

Value

a data list. It includes the data generated, true networks underlying the data, true tau. If type is heter, then true parameter alpha is included as well.

Index

CVlglasso, [2](#)

lglasso, [3](#)

Simulate, [6](#)